

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H01L 33/00, 25/16, G09F 9/33	A1	(11) International Publication Number: WO 97/24770
		(43) International Publication Date: 10 July 1997 (10.07.97)

(21) International Application Number: PCT/US96/19790


(22) International Filing Date: 17 December 1996 (17.12.96)

(30) Priority Data:
08/579,538 27 December 1995 (27.12.95) US(71) Applicant: SIEMENS COMPONENTS, INC. [US/US]; 10950
North Tantau Avenue, Cupertino, CA 95014 (US).(72) Inventor: LUMBARD, Marvin; 16445 Mozart Way, Los
Gatos, CA 95030 (US).(74) Agents: SMITH, Darryl, A. et al.; Siemens Corporation,
Intellectual Property Dept., 186 Wood Avenue South, Iselin,
NJ 08830 (US).(81) Designated States: JP, KR, SG, European patent (AT, BE, CH,
DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT,
SE).**Published***With international search report.**Before the expiration of the time limit for amending the
claims and to be republished in the event of the receipt of
amendments.*

(54) Title: SURFACE MOUNT LED ALPHANUMERIC DISPLAY

(57) Abstract

The heat tolerance of an LED alphanumeric display device (10) having a clear epoxy encapsulation (70) can be improved by matching the coefficient of thermal expansion (CTE) of the inner circuit board (120) to the high CTE of the epoxy. When heat is applied to fix the device to a circuit board, the components will expand at a nearly equal rate, avoiding cracking and failure.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

SURFACE MOUNT LED ALPHANUMERIC DISPLAYField of the Invention

This invention relates generally to LED alphanumeric
5 displays. Specifically, the invention is directed to a
surface-mounted LED alphanumeric display.

Background of the Invention

A desirable encapsulation for a surface mount device
10 is epoxy. Epoxy is well-suited to mass production molding,
providing a structurally sound and hermetically-sealed
enclosure for the encapsulated components. A surface-mount
device is installed by soldering it in place, requiring the
application of heat perhaps as high as 200°C which causes
15 the components of the display to expand. However, if the
respective coefficients of thermal expansion (CTE) of the
encapsulation, the circuit board, and other components
differ markedly, they will expand at proportionately
different rates, leading to stress and strain, causing the
20 device to crack and probably fail.

The heat problem for surface mount devices can be
dealt with in several ways. First, there is a generally-
accepted engineering practice of specifying printed circuit
board materials having a low CTE to match the CTE of the
25 copper traces on the circuit board within the device. This
will minimize expansion of the circuit board and avoid
cracking of the copper traces and other damage to the
device. Second, the expansion of the encapsulation can be
minimized by employing an opaque epoxy, which has a CTE
30 nearly equal to that of the encapsulated components. The
CTE of the epoxy can be further lowered by adding
impurities to the epoxy. Thus, when heat is applied, the
encapsulation and the components inside will expand at a
nearly-equal rate.

35 For some applications, it would be desirable to
provide an LED alphanumeric display in a surface-mount
configuration. The active display devices, related logic
circuitry, and the interconnecting leads would be placed on
a substrate such as a printed circuit board or flex

circuit, and the assembly would be encapsulated within a transparent enclosure. Since it is imperative that the encapsulation for a display device be transparent, opaque epoxies and impurities cannot be employed. Nevertheless, it would be desirable to encapsulate the device in epoxy. However, the required clear epoxy has a CTE considerably higher than that of the circuit boards, components, and interconnecting leads of the typical display device. If no provision is made for the high CTE of clear epoxy, the device will likely fail as a result of the heat from soldering.

To avoid failure due to uneven expansion of the various components and the clear epoxy encapsulation of the LED alphanumeric display, the composition of the components and encapsulation should be selected such that the coefficients of thermal expansion (CTE) of those components are equivalent or nearly so.

Summary of the Invention

The present invention obviates the aforementioned problem by matching or nearly matching the CTE of the circuit board to that of the clear epoxy, contrary to the generally accepted practice of matching the CTE of the epoxy to that of the components within the encapsulation. Advantageously, when heat is applied to the device, the inner components will expand at approximately the same rate as the clear epoxy encapsulation. The lead frame, although having a much lower CTE, makes minimal contact with the encapsulation and therefore essentially floats within the package and should not impose significant stress or strain on the device.

Brief Description of the Drawings

For a better understanding of the invention, reference is made to the following description of an exemplary embodiment thereof, and to the accompanying drawings, wherein:

Figure 1 is an sectional view of a surface-mount LED alphanumeric display having a flex circuit substrate;

Figure 2 is an sectional view of a surface-mount LED alphanumeric display having a plastic PCB substrate;

5 Figure 3 is an sectional view of a vertically-mounted LED alphanumeric display having a plastic PCB substrate; and

10 Figure 4 is a plan view of a surface-mount LED alphanumeric display and leadframes prior to encapsulation.

Detailed Description

Figure 1 shows a surface-mount LED alphanumeric display device 10 having a compliant, two-layer flex circuit 20. The flex circuit 20 is bonded or otherwise
15 attached to an Ultem stiffener 30. Ultem is a trademark for a General Electric material having a coefficient of thermal expansion (CTE) of approximately 60×10^{-6} ppm, selected because it has a CTE approximately equal to that of clear epoxy, although one could choose another material
20 having a nearly-equivalent CTE.

The device 10 has leads 40 for providing power and control to the device 10, two of which are visible in Figure 1. The leads 40 are provided with J-bends 42, which afford tight vertical stacking and mounting. Display
25 elements 50 are located on the top surface 22 of the flex circuit 20, while a CMOS logic device 60 is located on the under surface 24.

The flex circuit 20, the Ultem stiffener 30, the display elements 50, and the CMOS logic device 60 are enclosed in a clear epoxy encapsulation 70, while the
30 leads 40 are permitted to protrude out from the encapsulation 70.

In lieu of a compliant flex circuit, a plastic printed circuit board can be utilized as the substrate as
35 illustrated in Figure 2. As shown, a surface-mount LED alphanumeric display device 100 has a plastic printed circuit board (PCB) 120 having a CTE of approximately $60 \times$

10⁻⁶ ppm. The PCB 120 can be fabricated from Ultem material, which has such a CTE, or any other material having a nearly-equivalent CTE.

5 The device 100 also has leads 140 with J-bends 142, and display elements 150 and a CMOS logic device 160 mounted on opposite surfaces 122 and 124, respectively, of the PCB 120. As with the device of Figure 1, the PCB 120 is encased in an epoxy encapsulation 170 with protruding leads 140.

10 The device 100 of Figure 2 can be mounted vertically as shown in Figure 3. To maintain the device 100 in a vertical orientation, vertical stabilizers 180 can be provided to create a relatively stable rest on one side of the device. Similarly, the device 10 of Figure 1 could be
15 positioned vertically.

The device 10 is shown with leadframes 200 in Figure 4 prior to encapsulation. Visible to one side of the flex circuit 20 are the vertical stabilizers 180.

20 The device can be encapsulated using the closed mold described in co-pending U.S. patent application serial no. 08/xxx,xxx, filed December x, 1995, for a Closed-Mold LED alphanumeric display, assigned to the same assignee as the present application and incorporated herein by reference.

25 The embodiments described herein are merely illustrative of the principles of the present invention. Various modifications may be made thereto by persons ordinarily skilled in the art, without departing from the scope or spirit of the invention.

WHAT IS CLAIMED IS:

- 1 1. An LED alphanumeric display device, comprising:
2 a clear epoxy encapsulation, the epoxy having a
3 coefficient of thermal expansion; and
4 a circuit board containing at least one display
5 element, the circuit board having a coefficient of thermal
6 expansion approximately equal to the coefficient of thermal
7 expansion of the clear epoxy.
- 1 2. The device as set forth in claim 1, wherein the
2 circuit board comprises a flexible circuit affixed to a
3 stiffener.
- 1 3. The device as set forth in claim 2, wherein the
2 stiffener is fabricated from Ultem material.
- 1 4. The device as set forth in claim 1, wherein the
2 circuit board comprises a plastic circuit board.
- 1 5. The device as set forth in claim 4, wherein the
2 plastic circuit board is fabricated from Ultem material.
- 1 6. The device as set forth in claim 1, further
2 comprising leads connected to the circuit board, for
3 providing power and control to the device from at least one
4 external source.

1 7. An encapsulated LED alphanumeric display device,
2 comprising:
3 a clear epoxy encapsulation, the epoxy having a
4 coefficient of thermal expansion;
5 a circuit board containing at least one display
6 element and related logic circuitry, the circuit board
7 being a flexible circuit affixed to an Ultem stiffener and
8 the Ultem stiffener having a coefficient of thermal
9 expansion approximately equal to the coefficient of thermal
10 expansion of the clear epoxy; and
11 leads connected to the circuit board, for providing
12 power and control to the device from at least one external
13 source.

1 8. An encapsulated LED alphanumeric display device,
2 comprising:
3 a clear epoxy encapsulation, the epoxy having a
4 coefficient of thermal expansion;
5 a plastic printed circuit board containing at least
6 one display element and related logic circuitry, the
7 plastic printed circuit board having a coefficient of
8 thermal expansion approximately equal to the coefficient of
9 thermal expansion of the clear epoxy; and
10 leads connected to the circuit board, for providing
11 power and control to the device from at least one external
12 source.

1/2

FIG. 1




FIG. 2






FIG. 3



2/2

FIG. 4



INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 96/19790

A. CLASSIFICATION OF SUBJECT MATTER IPC 6 H01L33/00 H01L25/16 G09F9/33		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) IPC 6 H01L		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used)		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 567 814 A (SIEMENS COMPONENTS INC) 3 November 1993 see column 1, line 50 - column 2, line 14; figures 1,2 -----	1,6-8
<input type="checkbox"/> Further documents are listed in the continuation of box C. <input checked="" type="checkbox"/> Patent family members are listed in annex.		
* Special categories of cited documents :		
<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p>*A* document defining the general state of the art which is not considered to be of particular relevance</p> <p>*E* earlier document but published on or after the international filing date</p> <p>*L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>*O* document referring to an oral disclosure, use, exhibition or other means</p> <p>*P* document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="width: 45%;"> <p>*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>*A* document member of the same patent family</p> </div> </div>		
Date of the actual completion of the international search <div style="text-align: center; font-weight: bold;">21 April 1997</div>		Date of mailing of the international search report <div style="text-align: center; font-weight: bold;">15.05.97</div>
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax (+31-70) 340-3016		Authorized officer <div style="text-align: center; font-weight: bold;">De Laere, A</div>

Information on patent family members

PCT/US 96/19790

Form PCT/ISA/210 (patent family annex) (July 1992)